

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.01.2024

Version number 2 (replaces version 1)

Revision: 30.01.2024

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name: GRADI Fix PU Foam 750 ml BG-GB-GR**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**  
Assembly foam
- **Application of the substance / the mixture** Construction chemicals
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
GRADI  
Selena FM S.A.  
ul. Legnicka 48 A 54-202 Wrocław, Poland  
tel.: +48 71 78 38 290  
e-mail: office@selena.com  
www.selena.com  
BDO: 000136566
- **Further information obtainable from:** msds@selena.com
- **1.4 Emergency telephone number:** European emergency number: 112 (24h)

### SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Aerosol 1            H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS08 health hazard

Resp. Sens. 1    H334            May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
Carc. 2            H351            Suspected of causing cancer.  
STOT RE 2        H373            May cause damage to organs through prolonged or repeated exposure.



GHS07

Acute Tox. 4      H332            Harmful if inhaled.  
Skin Irrit. 2      H315            Causes skin irritation.  
Eye Irrit. 2       H319            Causes serious eye irritation.  
Skin Sens. 1      H317            May cause an allergic skin reaction.  
STOT SE 3        H335            May cause respiratory irritation.

Lact.              H362            May cause harm to breast-fed children.  
Aquatic Chronic 4 H413            May cause long lasting harmful effects to aquatic life.

- **Additional information:**

The classification of the preparation with the assignment of the phrase H413 taking into account the content of chlorinated alkanes C14-C17 was made on the basis of the study "FEICA Fact Sheet on the classification and labelling of one-component moisture curing polyurethane foams containing medium-chained chlorinated paraffins (MCCP)".

(Contd. on page 2)

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 30.01.2024

Version number 2 (replaces version 1)

Revision: 30.01.2024

Trade name: GRADI Fix PU Foam 750 ml BG-GB-GR

(Contd. of page 1)

- **2.2 Label elements**

- **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

- **Hazard pictograms**



GHS02    GHS07    GHS08

- **Signal word** Danger

- **Hazard-determining components of labelling:**

diphenylmethanediisocyanate, isomers and homologues  
chlorinated paraffins, C14-17

- **Hazard statements**

H222 Extremely flammable aerosol.  
H229 Pressurised container: May burst if heated.  
H332 Harmful if inhaled.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
H317 May cause an allergic skin reaction.  
H351 Suspected of causing cancer.  
H362 May cause harm to breast-fed children.  
H335 May cause respiratory irritation.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H413 May cause long lasting harmful effects to aquatic life.

- **Precautionary statements**

P102                    Keep out of reach of children.  
P260                    Do not breathe gas.  
P263                    Avoid contact during pregnancy and while nursing.  
P271                    Use only outdoors or in a well-ventilated area.  
P280                    Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.  
P302+P352            IF ON SKIN: Wash with plenty of water.  
P304+P340            IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P305+P351+P338    IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308+P313            IF exposed or concerned: Get medical advice/attention.  
P501                    Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Additional information:**

As from 24 August 2023 adequate training is required before industrial or professional use. Further information at: [www.feica.eu/PUinfo](http://www.feica.eu/PUinfo)

Do not pierce or burn, even after use.

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Do not spray on an open flame or other ignition source.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Persons already sensitised to diisocyanates may develop allergic reactions when using this product.

Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product.

This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

EUH204 Contains isocyanates. May produce an allergic reaction.

(Contd. on page 3)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.01.2024

Version number 2 (replaces version 1)

Revision: 30.01.2024

Trade name: GRADI Fix PU Foam 750 ml BG-GB-GR

(Contd. of page 2)

- 2.3 Other hazards
- Results of PBT and vPvB assessment

• **PBT:**

CAS: 85535-85-9 | chlorinated paraffins, C14-17

• **vPvB:**

CAS: 85535-85-9 | chlorinated paraffins, C14-17

• **Determination of endocrine-disrupting properties**

The product does not contain substances with endocrine disrupting properties.

### SECTION 3: Composition/information on ingredients

• **3.2 Mixtures**

- **Description:** Mixture of substances listed below with nonhazardous additions.

• **Dangerous components:**

CAS: 9016-87-9 EC number: 618-498-9	diphenylmethanediisocyanate, isomers and homologues ⚠ Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; ⚠ Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335, EUH204 Specific concentration limits: Skin Irrit. 2; H315: C ≥ 5 % Eye Irrit. 2; H319: C ≥ 5 % Resp. Sens. 1; H334: C ≥ 0.1 % STOT SE 3; C ≥ 5 %	20 - 60%
CAS: 85535-85-9 EINECS: 287-477-0 Index number: 602-095-00-X Reg.nr.: 01-2119519269-33-xxxx	chlorinated paraffins, C14-17 ⚠ Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=10); Lact., H362, EUH066 PBT; vPvB	< 30%
CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0 Reg.nr.: 01-2119485395-27-xxxx	isobutane ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280	< 15%
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-31-xxxx	butane, pure ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280	< 15%
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21-xxxx	propane ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280	< 15%
CAS: 115-10-6 EINECS: 204-065-8 Index number: 603-019-00-8 Reg.nr.: 01-2119472128-37-xxxx	dimethyl ether ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280	< 10%

• **SVHC**

CAS: 85535-85-9 | chlorinated paraffins, C14-17

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

• **4.1 Description of first aid measures**• **After inhalation:**

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

(Contd. on page 4)

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 30.01.2024

Version number 2 (replaces version 1)

Revision: 30.01.2024

Trade name: GRADI Fix PU Foam 750 ml BG-GB-GR

(Contd. of page 3)

- **After skin contact:**

Remove uncured foam using a piece of cloth and an unaggressive solvent, e.g. ethanol. Wash your hands and the cleaned skin surface using soapy water. Cured foam can be removed mechanically with the use of a brush, soap and plenty of water. Use protective cream after skin surface has been cleaned.

- **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- **After swallowing:**

Do not induce vomiting; call for medical help immediately.

Rinse out mouth and then drink plenty of water.

- **4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

- **4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

## SECTION 5: Firefighting measures

- **5.1 Extinguishing media**

- **Suitable extinguishing agents:**

Carbon dioxide.

Fire-extinguishing powder.

Foam.

Water spray.

Use fire extinguishing methods suitable to surrounding conditions.

- **For safety reasons unsuitable extinguishing agents:** Water with full jet.

- **5.2 Special hazards arising from the substance or mixture**

Can form explosive gas-air mixtures.

Formation of toxic gases is possible during heating or in case of fire.

- **5.3 Advice for firefighters**

- **Protective equipment:**

Wear fully protective suit.

Wear self-contained respiratory protective device.

## SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**

Keep away from ignition sources.

Wear protective clothing.

Ensure adequate ventilation.

- **6.2 Environmental precautions:**

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers / surface or ground water.

- **6.3 Methods and material for containment and cleaning up:**

Uncured foam adheres easily, hence it should be removed with caution. Remove instantly using a piece of cloth and solvents, e.g. acetone, alcohol. Remove cured foam mechanically.

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

- **6.4 Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**

Open and handle receptacle with care.

(Contd. on page 5)

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 30.01.2024

Version number 2 (replaces version 1)

Revision: 30.01.2024

Trade name: GRADI Fix PU Foam 750 ml BG-GB-GR

(Contd. of page 4)

Do not pierce or burn even after use. Use only as directed on the label.

Do not mix with any other chemical products.

Ensure good ventilation / exhaustion at the workplace.

- **Information about fire - and explosion protection:**

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- **7.2 Conditions for safe storage, including any incompatibilities**

- **Storage:**

- **Requirements to be met by storerooms and receptacles:**

This product is subject to regulations governing the storage of highly flammable aerosol products.

Storage rooms should be equipped with heat and smoke detectors.

Electrical equipment should be explosion-proof.

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

- **Information about storage in one common storage facility:**

Do not store together with acids.

Do not store together with alkalis (caustic solutions).

Store away from reducing agents.

Store away from oxidising agents.

Store away from foodstuffs.

Store away from plastic, rubber, aluminum, light-metals.

- **Further information about storage conditions:**

Store receptacle in a well ventilated area.

Store in vertical position in closed original containers.

Store at temperature from +5°C to +30°C.

Protect from frost.

Store under lock and key and out of the reach of children.

Protect from heat and direct sunlight.

- **7.3 Specific end use(s)** No further relevant information available.

## SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**

- **Ingredients with limit values that require monitoring at the workplace:**

<b>CAS: 9016-87-9 diphenylmethanediisocyanate, isomers and homologues</b>	
OEL (Ireland)	Short-term value: 0.07 mg/m <sup>3</sup> Long-term value: 0.02 mg/m <sup>3</sup> as -NCO; Sens.
<b>CAS: 75-28-5 isobutane</b>	
OEL (Ireland)	Short-term value: 1000 ppm
<b>CAS: 74-98-6 propane</b>	
OEL (Ireland)	Asphx
<b>CAS: 115-10-6 dimethyl ether</b>	
IOELV (EU)	Long-term value: 1920 mg/m <sup>3</sup> , 1000 ppm
OEL (Ireland)	Long-term value: 1920 mg/m <sup>3</sup> , 1000 ppm IOELV
<b>CAS: 106-97-8 butane, pure</b>	
OEL (Ireland)	Short-term value: 1000 ppm

(Contd. on page 6)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.01.2024

Version number 2 (replaces version 1)

Revision: 30.01.2024

Trade name: GRADI Fix PU Foam 750 ml BG-GB-GR

(Contd. of page 5)

- **Regulatory information**

OEL (Ireland): 2021 CoP for the Safety, Health and Welfare at Work  
IOELV (EU): (EU) 2019/1831

- **DNELs**

**CAS: 9016-87-9 diphenylmethanediisocyanate, isomers and homologues**

Oral	DNEL	20 mg/kg/day (General population, consumers)
Dermal	DNEL	0.05 mg/kg/day (General population, consumers)
Inhalative	DNEL	0.05 mg/m <sup>3</sup> (General population, consumers) 0.05 mg/m <sup>3</sup> (Workers)

**CAS: 85535-85-9 chlorinated paraffins, C14-17**

Oral	DNEL	0.115 mg/kg/day (General population, consumers)
Dermal	DNEL	5.75 mg/kg/day (General population, consumers) 11.5 mg/kg/day (Workers)
Inhalative	DNEL	0.4 mg/m <sup>3</sup> (General population, consumers) 1.6 mg/m <sup>3</sup> (Workers)

**CAS: 115-10-6 dimethyl ether**

Inhalative	DNEL	471 mg/m <sup>3</sup> (General population, consumers) 1,894 mg/m <sup>3</sup> (Workers)
------------	------	--

- **PNECs**

**CAS: 9016-87-9 diphenylmethanediisocyanate, isomers and homologues**

(freshwater)	1 mg/l
(sea water)	0.1 mg/l
(soil)	1 mg/kg

**CAS: 85535-85-9 chlorinated paraffins, C14-17**

(freshwater)	1 mg/l
(sea water)	0.2 mg/l
(freshwater sediments)	13 mg/kg
(sea water sediments)	2.6 mg/kg
(soil)	20 mg/kg

**CAS: 115-10-6 dimethyl ether**

(freshwater)	0.155 mg/l (Aquatic Organisms)
(sea water)	0.016 mg/l (Aquatic Organisms)
(freshwater sediments)	0.681 mg/kg (Aquatic Organisms)
(sea water sediments)	0.069 mg/kg (Aquatic Organisms)
(soil)	0.045 mg/kg (Terrestrial Organism)

- **Additional information:** The lists valid during the making were used as basis.

- **8.2 Exposure controls**

- **Appropriate engineering controls** No further data; see section 7.

- **Individual protection measures, such as personal protective equipment**

- **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing.  
Wash hands before breaks and at the end of work.  
Avoid contact with the eyes and skin.  
Do not inhale gases / fumes / aerosols.

- **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

(Contd. on page 7)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.01.2024

Version number 2 (replaces version 1)

Revision: 30.01.2024

Trade name: GRADI Fix PU Foam 750 ml BG-GB-GR

(Contd. of page 6)

- **Hand protection**



Protective gloves

EN 374

The glove material has to be impermeable and resistant to the product / the substance / the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

- **Material of gloves**

Polyethylene gloves.

Recommended thickness of the material:  $\geq 0.02$  mm.

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

Short-term contact  $\geq 10$  min (EN 374)

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye/face protection**



Tightly sealed goggles

EN 166

- **Body protection:** Protective work clothing.

## SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**

- **General Information**

· <b>Physical state</b>	Liquid
· <b>Colour:</b>	Different according to colouring
· <b>Odour:</b>	Characteristic
· <b>Odour threshold:</b>	Not determined
· <b>Melting point/freezing point:</b>	Not determined
· <b>Boiling point or initial boiling point and boiling range</b>	Not applicable, as aerosol
· <b>Flammability</b>	Extremely flammable aerosol.
· <b>Lower and upper explosion limit</b>	
· <b>Lower:</b>	1.5 Vol %
· <b>Upper:</b>	11.0 Vol %
· <b>Flash point:</b>	< 0 °C
· <b>Auto-ignition temperature:</b>	Not specified
· <b>Decomposition temperature:</b>	Not determined
· <b>pH</b>	Not applicable
· <b>Viscosity:</b>	
· <b>Kinematic viscosity</b>	Not determined

(Contd. on page 8)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.01.2024

Version number 2 (replaces version 1)

Revision: 30.01.2024

Trade name: GRADI Fix PU Foam 750 ml BG-GB-GR

(Contd. of page 7)

- **Solubility**

- **water:** Insoluble  
Reacts with water

- **Partition coefficient n-octanol/water (log value)**

Not determined

- **Vapour pressure:**

>500 kPa (in the container)  
< 1\*10<sup>-5</sup> mmHg w 25°C (MDI)

- **Density and/or relative density**

- **Density at 20 °C:**

≤ 1.3 (PMDI) g/cm<sup>3</sup>

- **Relative density**

Not determined

- **Relative gas density**

Void

- **Particle characteristics**

Void

- **9.2 Other information**

- **Appearance:**

- **Form:**

Rapidly curing foam dispensed by gaseous propellant from an aerosol container

- **Important information on protection of health and environment, and on safety.**

- **Ignition temperature:**

&gt; +350 °C (propellant)

- **Explosive properties:**

Heating may cause an explosion.

- **Information with regard to physical hazard classes**

- **Explosives**

Void

- **Flammable gases**

Void

- **Aerosols**

Extremely flammable aerosol.  
Pressurised container: May burst if heated.

- **Oxidising gases**

Void

- **Gases under pressure**

Void

- **Flammable liquids**

Void

- **Flammable solids**

Void

- **Self-reactive substances and mixtures**

Void

- **Pyrophoric liquids**

Void

- **Pyrophoric solids**

Void

- **Self-heating substances and mixtures**

Void

- **Substances and mixtures, which emit flammable gases in contact with water**

Void

- **Oxidising liquids**

Void

- **Oxidising solids**

Void

- **Organic peroxides**

Void

- **Corrosive to metals**

Void

- **Desensitised explosives**

Void

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.

- **10.2 Chemical stability**

- **Thermal decomposition / conditions to be avoided:**

No decomposition if used according to specifications.

- **10.3 Possibility of hazardous reactions** No dangerous reactions known.

(Contd. on page 9)



## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.01.2024

Version number 2 (replaces version 1)

Revision: 30.01.2024

Trade name: GRADI Fix PU Foam 750 ml BG-GB-GR

(Contd. of page 8)

- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:**  
Strongly reacts with water and other substances containing an active hydrogen atom.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

### SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

- **Acute toxicity**

Harmful if inhaled.

- **LD/LC50 values relevant for classification:**

**CAS: 9016-87-9 diphenylmethanediisocyanate, isomers and homologues**

Oral	LD50	>10,000 mg/kg (rat) (OECD401)
Dermal	LD50	>9,400 mg/kg (rabbit) (OECD402)
Inhalative	LC50/4h	1.5 mg/l (ATE)

**CAS: 85535-85-9 chlorinated paraffins, C14-17**

Dermal	LD50	4,000 mg/kg (rat)
Inhalative	LC50	>3,300 mg/l (rat)

- **Skin corrosion/irritation**  
Causes skin irritation.
- **Serious eye damage/irritation**  
Causes serious eye irritation.
- **Respiratory or skin sensitisation**  
May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
May cause an allergic skin reaction.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity**  
Suspected of causing cancer.
- **Reproductive toxicity**  
May cause harm to breast-fed children.
- **STOT-single exposure**  
May cause respiratory irritation.
- **STOT-repeated exposure**  
May cause damage to organs through prolonged or repeated exposure.
- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **11.2 Information on other hazards**

- **Endocrine disrupting properties**

None of the ingredients is listed.

### SECTION 12: Ecological information

- **12.1 Toxicity**

- **Aquatic toxicity:**

**CAS: 9016-87-9 diphenylmethanediisocyanate, isomers and homologues**

EC50	1,640 mg/l (algae)
	>1,000 mg/l (daphnia) (OECD202)
	>100 mg/l (Sedimentation) (OECD209)
LC50	>1,000 mg/l (fish) (OECD)

**CAS: 85535-85-9 chlorinated paraffins, C14-17**

EC50	>3.2 mg/l (algae) (OECD 201)
------	------------------------------

(Contd. on page 10)

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 30.01.2024

Version number 2 (replaces version 1)

Revision: 30.01.2024

Trade name: GRADI Fix PU Foam 750 ml BG-GB-GR

(Contd. of page 9)

LC50	0.006 mg/l (daphnia) >5,000 mg/l (fish)
<ul style="list-style-type: none"> <li>· <b>12.2 Persistence and degradability</b> Not biodegradable.</li> <li>· <b>12.3 Bioaccumulative potential</b> Does not accumulate in organisms.</li> <li>· <b>12.4 Mobility in soil</b> No further relevant information available.</li> <li>· <b>12.5 Results of PBT and vPvB assessment</b></li> </ul>	
· <b>PBT:</b>	
CAS: 85535-85-9	chlorinated paraffins, C14-17
· <b>vPvB:</b>	
CAS: 85535-85-9	chlorinated paraffins, C14-17
<ul style="list-style-type: none"> <li>· <b>12.6 Endocrine disrupting properties</b> The product does not contain substances with endocrine disrupting properties.</li> <li>· <b>12.7 Other adverse effects</b></li> <li>· <b>Additional ecological information:</b></li> <li>· <b>General notes:</b> Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water. Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.</li> </ul>	

### SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.  
Dispose of in a safe manner in accordance with local / national regulations.  
Do not allow to enter surface or ground water.

Assigning a code from the waste catalogue depends on the sector, in which the user operates, as well as on arrangements made between the waste generator and a competent environment protection department.

- **European waste catalogue**

15 01 11*	metallic packaging containing a hazardous solid porous matrix (for example asbestos), including empty pressure containers
HP3	Flammable
HP4	Irritant - skin irritation and eye damage
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
HP7	Carcinogenic
HP13	Sensitising
HP14	Ecotoxic

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

### SECTION 14: Transport information

- |                                       |               |
|---------------------------------------|---------------|
| · <b>14.1 UN number or ID number</b>  |               |
| · <b>ADR, IMDG, IATA</b>              | UN1950        |
| · <b>14.2 UN proper shipping name</b> |               |
| · <b>ADR</b>                          | 1950 AEROSOLS |
| · <b>IMDG, IATA</b>                   | AEROSOLS      |

(Contd. on page 11)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.01.2024

Version number 2 (replaces version 1)

Revision: 30.01.2024

Trade name: GRADI Fix PU Foam 750 ml BG-GB-GR

(Contd. of page 10)

· **14.3 Transport hazard class(es)**

· **ADR**



· **Class** 2 5F Gases.  
 · **Label** 2.1

· **IMDG, IATA**



· **Class** 2.1 Gases.  
 · **Label** 2.1

· **14.4 Packing group** Not applicable.

· **14.5 Environmental hazards:**

· **Marine pollutant:** No.

· **14.6 Special precautions for user** Warning: Gases.

· **EMS Number:** F-D,S-U

· **14.7 Maritime transport in bulk according to IMO instruments** Not applicable.

· **Transport/Additional information:**

· **ADR**

· **Remarks:** Exemption from ADR provisions by LQ principal (rule 3.4)  
 - Inner packaging, max. 1 liter in capacity; outer packaging – max. gross weight of 30kg.  
 - Inner packaging, max. 1 liter in capacity, based on common ground and covered with shrink film – max. gross weight of 20kg.

· **UN "Model Regulation":** UN 1950 AEROSOLS, 2.1

### SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

1907/2006/CE Regulation, REACH  
 1272/2008/CE Regulation, CLP  
 2020/878/UE Regulation

· **Directive 2012/18/EU**

· **Named dangerous substances - ANNEX I** None of the ingredients is listed.

· **Seveso category** P3a FLAMMABLE AEROSOLS

· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t

· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t

(Contd. on page 12)

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 30.01.2024

Version number 2 (replaces version 1)

Revision: 30.01.2024

Trade name: GRADI Fix PU Foam 750 ml BG-GB-GR

(Contd. of page 11)

- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3, 56, 74

- **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

- **REGULATION (EU) 2019/1148**

- **Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))**

None of the ingredients is listed.

- **Annex II - REPORTABLE EXPLOSIVES PRECURSORS**

None of the ingredients is listed.

- **Regulation (EC) No 273/2004 on drug precursors**

None of the ingredients is listed.

- **Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors**

None of the ingredients is listed.

- **REGULATION (EC) No 1005/2009 on substances that deplete the ozone layer – ANNEX I (Ozone- depleting potential)**

- **Other regulations, limitations and prohibitive regulations**

- **Substances of very high concern (SVHC) according to REACH, Article 57**

CAS: 85535-85-9 chlorinated paraffins, C14-17

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

### · Relevant phrases

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H351 Suspected of causing cancer.

H362 May cause harm to breast-fed children.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH204 Contains isocyanates. May produce an allergic reaction.

- **Version number of previous version:** 1

### · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

(Contd. on page 13)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.01.2024

Version number 2 (replaces version 1)

Revision: 30.01.2024

**Trade name: GRADI Fix PU Foam 750 ml BG-GB-GR**

(Contd. of page 12)

LD50: Lethal dose, 50 percent  
PBT: Persistent, Bioaccumulative and Toxic  
SVHC: Substances of Very High Concern  
vPvB: very Persistent and very Bioaccumulative  
ATE: Acute toxicity estimate values  
Flam. Gas 1A: Flammable gases – Category 1A  
Aerosol 1: Aerosols – Category 1  
Press. Gas (Comp.): Gases under pressure – Compressed gas  
Acute Tox. 4: Acute toxicity – Category 4  
Skin Irrit. 2: Skin corrosion/irritation – Category 2  
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2  
Resp. Sens. 1: Respiratory sensitisation – Category 1  
Skin Sens. 1: Skin sensitisation – Category 1  
Carc. 2: Carcinogenicity – Category 2  
Lact.: Reproductive toxicity – effects on or via lactation  
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3  
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2  
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1  
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1  
Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard – Category 4

**\* Data compared to the previous version altered.**

Points marked with \* have changed from the previous version of the card